



Brings you the best in Retail Technology

E-Touch Jade 365

The E-Touch Jade 360 series is an innovative “Fan-less” design that operates at low noise, low power consumption and minimal maintenance. Tool-less modular construction is easy to maintain and service, and therefore significantly reduces total cost of ownership. Its small footprint and VESA wall-mountable features are ideal for applications where space is at a premium.

- Low power consumption and fan-less for quiet operation
- Easy access mechanical design for HDD and Compact Flash maintenance and upgrades
- Integrated wall-mount VESA design for wall mount applications
- Optional peripherals such as MSR, Programmable Keypad, Customer Display and 2nd Display are available for challenging operating environments
- All-in-one MB design for I/O card and cable material cost



FEATURES



Low power consumption and fan-less design for quiet operation



Small footprint 280 (W) x 250 (D)



Easy HDD & Motherboard access



Integrated wall mount VESA design for wall mount application



Specification

Model Name	E-Touch Jade 362	E-Touch Jade 365
Mainboard	B68	C48
Processor	Intel® Atom™ N270 Processor 1.6 GHz L2 512K FSB 533MHz	Intel® Pineview D525 Dual Core™ 1.8G L2 1M, FSB 800MHz
Chipset	Intel® 945GSE Express + ICH 7M	CPU with Graphic built-in + ICH 8M
System Memory	2 x DDR2 DIMM up to 2GB	2 x DDR3 DIMM up to 4GB, FSB 800MHz
Graphic Memory	Intel® GMA 950, share system memory up to 224MB	Intel® GMA 3150, share system memory up to 256MB
LCD Touch Panel		
LCD Size	POS 362: 12" TFT LCD POS 365: 15" TFT LCD	
Brightness	POS 362: 150 ~ 500 cd/m ² POS 365: 250 cd/m ²	
Resolution	POS 362: 800x600 / 1024x768 POS 365: 1024x768	
Touch Screen	Resistive	
Tilt Adjustment	-25° ~ 65°	
Storage Device		
Hard Drive	1 x 2.5" SATA bay	
Flash Memory	Compact Flash memory or SSD Solid State Drive (option)	
Expansion		
PCI-E Socket	1	
External I/O Port		
USB Port	4 x USB 2.0	
Serial Port	4 x RJ-45 COM (COM 3 / COM 4 pin 9 with 5V/12V)	
Parallel Port	1 (D-sub 25-pin)	
LAN Port	1 RJ-45 (10/100Mbps Giga LAN)	
Second Display	1	
Cash Drawer Port	1 x RJ-11 (12V/24V cash drawer)	
Audio Mic-in	1	
Audio Line-out	1	

Control / Indicator	
Power Button	1
LED Indicator	1
Power	Adapter (DC 90W, 19V, 4.7A)
Peripheral	
Magnetic Card Reader	3 Track (PS/2)
2 in 1 MSR	MSR (PS/2) + iButton (PS/2) / MSR (PS/2) + Finger Print (USB)
Second Display	10.4" / 12.1" TFT LCD display
Customer Display	VFD display 2 x 20 characters
Certificate	
EMC & Safety	FCC Class A / CE Marking / LVD
Environment	
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
Storage Temperature	-20°C ~ 55°C (-4°F ~ 140°F)
Operating Humidity	20% ~ 85% RH non-condensing
Storage Humidity	20% ~ 85% RH non-condensing
Dimension (W x D x H)	POS 362: 308 x 265 x 325 mm (12.1" x 10.4" x 12.8") POS 365: 385 x 265 x 384 mm (15.2" x 10.4" x 15.1")
Weight	POS 362: 7.5kg (16.5lbs) POS 365: 10kg (22lbs)
OS Supported	Windows® XP, WEPOS, POSReady 2009, XP Embedded, XP professional for Embedded, Linux, Vista®, Windows® 7, WIN CE



Shweta POS Systems
501, Gopal Towers,
Near Maninagar RLY Station,
Maninagar,
Ahmedabad – 380008
Gujarat
Tel: +91-9099094199

E-mail: sales@shwetapossystem.com
Web: www.shwetapossystems.com

