



Brings you the best in Retail Technology

E-touch Integrated 465

The E-Touch Integrated 460 Series is ideal for easy Service and Upgrade at an affordable price. A choice of 12.1", 15" and 17" Touch Screens with a tilt angle from 0° ~ 60° offers you maximum flexibility and convenience. All I/O connectors are under the rear cover to provide easier maintenance and better cable management.

Choice between P4, Celeron M, Dual Core Processors

Choice of OS's from Windows® XP, WEPOS, XP Embedded, XP prof. Embedded, WIN 2000 prof Embedded, Linux, Vista® (for C48), Windows® 7 (for C48), WIN CE.net (for C48)



FEATURES



1. Tilt Angle 0° ~ 60° degree



2. Magnetic Strip Card Reader, Finger Print and I-button module supportive



3. Thumb screw design easy to open rear cover



4. Easy to maintain and service
Less than 4 screws to reach key components



5. Customer display pole type
VFD type (2 x 20)
LCD type (graphic)



6. Front I/O cover

E-touch Integrated 465

Model Name	E-Touch Integrated 460	
Mainboard	B81	C48
Processor	mP478-Pin CPU socket FSB 400MHz, Celeron® M 1.2G, Celeron® 2.0G / 2.5G, P4 2.0G	Intel® Pineview D525 Dual Core™ 1.8G L2 1M, FSB 800MHz
Chipset	Intel® 852GM + ICH4	CPU with Graphic built-in + ICH 8M
System Memory	2 x 184-pin DIMM socket DDR 200 / 266MHz up to 2GB	2 x DDR3 DIMM up to 4GB, FSB 800MHz
Graphic Memory	Share System Memory up to 64MB	Intel® GMA 3150, share system memory up to 256 MB
LCD Size	POS 462 : 12.1" TFT LCD, 150-400 cd/m ² , 800x600	
Brightness	POS 465 : 15" TFT LCD, 250-350 cd/m ² , 1024x768	
Resolution	POS 467 : 17" TFT LCD, 300 cd/m ² , 1280x1024	
Touch Screen	Resistive	
Tilt Adjustment	0° ~ 60°	
Hard Drive	1 x 3.5" HDD	1 x 3.5" SATA HDD
Flash Memory	N/A	Optional Compact Flash function board, optional SSD
Mini-PCI Socket	1	
USB Port	2 x USB 2.0	1 x USB 2.0
PS/2 keyboard / mouse	1 x PS/2 keyboard	1 x PS/2 keyboard
	1 x PS/2 mouse	N/A
Multi-media Ports	N/A	1 Line in / Line Out
USB Port	2 x USB 2.0	4 ports (V2.0)
Serial Port	4 x Powered COM (pin1/pin9 with 5V/12V power)	4 x RJ45 COM (COM3, COM4 with 5V/12V power)
Parallel Port	1 x Parallel Port	
LAN Port	1 x RJ45 10/100Mbps Giga LAN	1 x RJ45 (10 / 100 / 1000 Mbps Giga LAN)
Second Display	1 x Female type connector with Power	
Cash Drawer Port	2 x RJ (12V / 24V)	1 x RJ11 (12V/24V)
24V Print / DC Jack	N/A	DC Jack
Power Button	1 x Power On / Off	
Indicator LED	1 x LED (Green)	
Power	Internal 250W ATX	External 19V, 90W
EMC & Safety	FCC / CE Class A, LVD	
Operating Temperature	5°C ~ +35°C (41°F ~ +95°F)	
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	
Operating Humidity	20% ~ 80% RH non condensing	
Storage Humidity	20% ~ 85% RH non condensing	
MSR	3 Tracks MSR (PS/2) - (Serial Option)	
2-in-1 MSR	MSR (PS/2 / COM) + Finger Print (USB)	
3-in-1 MSR	MSR (PS/2 / COM) + Smart IC card (USB) + iButton (PS/2 / COM)	
Second Display	8.4" / 10.4" / 12.1" TFT LCD	
Customer Display	VFD / LCD	
Wireless LAN	Mini PCI 802.11 a/b/g Wi-Fi card and antenna	
Dimension (W x D x H)	LCD 0° tilt angle	
	POS 462 : 324.8 x 180.1 x 344.2 mm / 12.8" x 7.1" x 13.6"	
	POS 465 : 378 x 180.1 x 358.5 mm / 14.9" x 7.1" x 14.1"	
Weight	POS 467 : 410 x 192.8 x 373.7 mm / 16.1" x 7.6" x 14.7"	
	POS 462 : 8kg (17.6lbs), POS 465 : 9kg (19.8lbs), POS 467 : 10kg (24.2lbs)	
OS Supported	Windows® XP, WEPOS, XP Embedded, XP professional for Embedded, WIN 2000 professional Embedded, Linux, Vista® (for C48), Windows® 7 (for C48), WIN CE (for C48)	



SAM4S

Metrologic

MAGTEK

AccuBANKER



Staff on time®

GODEX



E-PoS Systems (India) Pvt Ltd.,
B-6, Punit Industrial premises,
Thane Belapur Road, MIDC Turbhe,
Navi Mumbai 400705
India
Tel No. (+91) 22 27631680
Fax NO. (+91) 22 27631670

E-Mail: sales@eposindia.co.in
Web Site: www.eposintl.com
www.eposindia.co.in

