



Brings you the best in Retail Technology

GP-2120T

Direct Thermal Label & Barcode Printer



EASY OPERATION, EASY MAINTENANCE!

Features

- 2M DRAM Memory
- 2" Inch Paper Width
- Compatible with Various Label Softwares
- Module Design for Different Applications
- Label paper Auto Positioned
- Thermal Continuous & Sticker Paper supported
- BMP, PCX & BAS Images download supported
- Parallel, Serial, USB Ethernet Interface Options
- Print head Pressure Adjustable
- Label paper Peel-Off & Tear-Off modes supported
- Temperature Auto Controlled



Specifications:

Print method	Direct thermal line
Resolution	203DPI
Character	FONT 0 to FONT 8 Simplified Chinese, Traditional Chinese and Korean
Barcode type	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPCE+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14
Print speed	Max.127mm/s Min.101mm/s
Memory	DRAM: 2M FLASH: 2M
Print head temperature sensor	Thermal Sensitive Resistance
Print head position sensor	Microswitch
Interface	Parallel/Serial+USB/Ethernet
Print width	2inch
Paper width	20-60mm
Paper diameter	110mm
Power supply	DC 12V/3A
Paper off mode	Tear off or Peel off
Work environment	Temperature: 0~45℃, Humidity: 10~80%
Storage environment	Temperature: -10~60%, Humidity: 10~90%
Dimension	110 × 220 × 160mm (W×D×H)
Weight	1.1Kg

Serial+USB



Parallel



LAN



Shweta POS Systems
501, Gopal Towers,
Near Maninagar RLY Station,
Maninagar,
Ahmedabad – 380008
Gujarat
Tel: +91-9099094199

E-mail: sales@shwetapossystem.com
Web: www.shwetapossystems.com


shweta
 POS SYSTEMS

