



RFID Consumables



RFID Cards For Proximity Readers, Read Only

PCR340 is a simple to use device applying dual 125KHz and 13.56MHz RFID technology to read the unique serial number of the RFID card. It is good to be used for access log on/log off key and the system operator identification.

Advantages

- Read either 125KHz or 13.56MHz frequency cards
- Designed with RS232 or PS/2 or USB interface
- Read unique serial number (UID) of the RFID card
- System log on / log off
- Verify ID code for the system operator identification. In addition to the ID code data, the prefix or/and postfix characters can be set too
- Cradle design to accept RFID card for the application as bellow:
 - System is workable when the registered card is sitting on the cradle
 - System is workable when the registered card is removed from the cradle

RFID CARDS FOR PROXIMITY READERS, READ ONLY	
CFR03	2mm thickness with Random ID Number
CFR01	ISO standard 0.8mm Thickness with random ID Number
CFR03S	2mm Thickness with customer specified or sequential number
CFR01S	ISO standard 0.8mm with customer specified or sequential number
RFID DISC TAG FOR PROXIMITY READER	
TAG52	Disc with diameter 52mm, inner hole 5.1mm, thickness 8mm
TAG50A	Disc with diameter 50mm, inner hole 4mm, thickness 2.4mm Available in Gray color only
TAG25	Disc with diameter 25mm, thickness 4mm
TAG22	Disc with diameter 22mm, thickness 3.2mm
TAG25K	Key Chain, W 31 x H 41 x D 5mm
TAG20KD	Tear drop key chain, W 30 x H 45.2 x D 5.1mm
TAG20KG	Tear drop key chain, W 30 x H 45.2 x D 5.1mm

E-POS International LLC
 P.O. Box : 44960 Dubai, U.A.E.
 Tel. : +971 4 3523288, 3512861
 Fax : +971 4 3513396
 E-mail : sales@eposintl.com www.eposintl.com

Our Business Partner